(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau

(43) International Publication Date 15 January 2004 (15.01.2004)

PCT

(10) International Publication Number WO 2004/006273 A1

(51) International Patent Classification7:

H01C 7/13

(74) Agent: YOON, Jee Hong; Hannuri Bldg., 219 Naeja-

(21) International Application Number:

PCT/KR2002/001295

(22) International Filing Date:

9 July 2002 (09.07.2002)

(25) Filing Language:

Korean

(26) Publication Language:

English

(71) Applicant (for all designated States except US): SMART ELECTRONICS INC. [KR/KR]; 1406 Joil-ri, Samdongmyun, Ulju-gun, 689-934 Ulsan (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KIM, Young Sun [KR/KR]; Daelim Apt. 115-801, 1406 Choa-dong, Haeundae-gu, 612-030 Pusan (KR). KANG, Doo Won [KR/KR]; Ssangyoung Apt. 102-1004, Chung ryang-myun, Ulju-gun, 689-860 Ulsan (KR). AHN, Gyu Jin [KR/KR]; Sam Apt. 102-505, 56522 Banggi-ri, Samnam-myun, Ulju-gun, 689-813 Ulsan (KR). NOH, Jin Seok [KR/KR]; Baekyang Green Apt. 202-1312, 522 Mora 3-dong, Sasang-gu, 617-817 Pusan (KR).

dong, Chongno-gu, 110-053 Seoul (KR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,

AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FUSIBLE RESISTOR AND METHOD OF FABRICATING THE SAME



(57) Abstract: A fusible resistor and method of fabricating the same is provided. The fusible resistor has a very low resistance of 20 to $470m\Omega$ by depositing thin films as a fusible element made of a material with low resistivity such as copper having a temperature coefficient of over 2,000 ppm/°C. The fusible resistor comprises a resistor body, a fusible element layer formed to surround the resistor body, caps formed to surround ends of the fusible element layer, lead wires attached to the caps, and an insulating layer for insulating the fusible element layer and the caps from outside. The thus-fabricated fusible resistor performs all functions of a use without generating excessive heat.